

**NEW**

# CT-MultiCom

- Protection class IP65 and IP67
- Rugged Nexus socket
- 2 volume keys
- Impact- and flame-resistant
- Operating temperature: -30 °C to +70 °C
- Two PTT buttons
- Emergency call button
- 3.5 mm jack socket



WHEN IT COUNTS

## CT-MultiCom

Made in Germany  Developed and designed in Germany

IP Equal to protection class IP65 and IP67



Series **4** CT-Modular „Series 4“ with Nexus socket/connector for the headset



 Flame-resistant

 Nexus plug connection (4-pole)

## CT-MultiCom



### The new CT-MultiCom: more than just a hand mike

The CT-MultiCom communications device represents a new and compact addition to the CeoTronics family of remote speaker mic. Housed in an impact- and flame-resistant housing, the CT-MultiCom is well-shielded from environment influences with its IP65 and IP67 protection class. Both dust-tight and waterproof, the speaker mic offers plenty of useful functions for fire fighter teams.

In addition to a 3.5 mm jack socket for connecting a CT earphone with sound tube, users can also connect a variety of professional CT headset systems via the ruggedized Nexus jack socket – such as systems from the CT-Modular „Series 4“.

As an especially user-friendly feature, the CT-MultiCom comes with two PTT buttons that are easy to operate even when wearing gloves. Loudspeaker volume can be adjusted using two separately housed keys to one of three levels to suit user preferences – or muted as required. For the safety of the users, the CeoTronics speaker mic is equipped with an emergency button

The CT-MultiCom is factory-fitted with a 12-pin Hirose connector and 230 mm spiral cable. Customers can choose from a wide range of 12-pin adapters for connection to radio equipment.

Talk to our experienced area sales manager for details!

### Technical Data

|                       |                                     |
|-----------------------|-------------------------------------|
| Weight total          | 245 g                               |
| Dimensions (L/W/H)    | 100 mm x 71 mm x 30 mm              |
| Microphone type       | Electret (noise-compensating)       |
| Operating temperature | - 30 °C – + 70 °C                   |
| Plastic housing       | Impact- and flame-resistant         |
| LED status indicator  | Yes                                 |
| Connections           | Headset – Nexus 7.11 mm             |
|                       | Earphone – 3.5 mm jack              |
|                       | Radio – 12-pin Hirose (via Adapter) |

|         |                                               |
|---------|-----------------------------------------------|
| Buttons | Front PTT                                     |
|         | Side PTT                                      |
|         | Emergency call button (if supported by radio) |
|         | 2 volume control keys                         |
|         | Loudspeaker mute / unmute                     |





## CeoTronics AG

Audio · Video · Data Communication

Adam-Opel-Str. 6  
63322 Rödermark (Germany)

Tel.: +49 6074 8751-0  
Fax: +49 6074 8751-265  
E-Mail: [sales@ceotronics.com](mailto:sales@ceotronics.com)  
Web: [www.ceotronics.com](http://www.ceotronics.com)